


Pipe Couplings

DN mm	Pipe o.d. in mm	Tol. On o.d. for length L in mm	L mm	A mm	B mm	Sleeve C x av. Thickness in mm	Bolts & nuts Qty. x dia. x length	Weight kg	WP bar
50	60,3	+/- 0,8	100	89	147	80 x 4,8	2 x M12 x 140 mm	2,5	46
65	76,1	+/- 0,8	100	155	172	100 x 6,0	2 x M12 x 165 mm	2,6	46
80	88,9	+/- 0,8	100	153	172	100 x 7,1	3 x M12 x 165 mm	3,2	46
100	114,3	+/- 0,8	100	178	172	100 x 7,1	3 x M12 x 165 mm	3,3	46



Pipe Couplings

DN mm	Pipe o.d. in mm	Tol. On o.d. for length L in mm	L mm	A mm	B mm	Sleeve C x av. Thickness in mm	Bolts & nuts Qty. x dia. x length	Weight kg	WP bar
125	139,7	+ 1,6 - 0,8	100	228	175	100 x 6	4 x M12 x 165 mm	4,8	46
150	168,3	+ 1,6 - 0,8	100	256	175	100 x 6	4 x M12 x 165 mm	8,6	37
200	219,1	+ 1,6 - 0,8	100	313	175	100 x 6	6 x M12 x 165 mm	10,9	36
250	273,1	+ 1,6 - 0,8	100	370	175	100 x 6	6 x M12 x 165 mm	13,3	35
300	323,9	+ 1,6 - 0,8	100	421	175	100 x 6	6 x M12 x 165 mm	15,3	35
350	355,6	+ 2,4 - 0,8	150	452	239	150 x 6	6 x M12 x 165 mm	18	26
400	406,4	+/- 1,6	150	503	239	150 x 6	8 x M12 x 230 mm	20	26
450	457,2	+/- 1,6	150	554	239	150 x 6	8 x M12 x 230 mm	24	26
500	508	+/- 1,6	150	605	239	150 x 6	10 x M12 x 230 mm	25	26
550	558,8	+/- 1,6	150	655	239	150 x 6	10 x M12 x 230 mm	30	26
600	609,6	+/- 1,6	150	707	239	150 x 6	10 x M12 x 230 mm	32	24
650	660,4	+/- 1,6	150	757	239	150 x 6	12 x M12 x 230 mm	42	24
700	711,2	+/- 1,6	150	812	240	150 x 6	14 x M12 x 230 mm	47	24
800	812,8	+/- 1,6	150	914	240	150 x 6	14 x M12 x 230 mm	53	20
900	914,4	+/- 1,6	150	1015	265	150 x 6	16 x M12 x 230 mm	56	20
1000	1016	+/- 1,6	150	1117	265	150 x 6	18 x M12 x 230 mm	71	16
1200	1219,2	+/- 1,6	150	1346	265	150 x 6	22 x M12 x 230 mm	118	16